§74.2706

Azobenzene, not more than 40 parts per bil-

Benzidine, not more than 1 part per billion. 1,3-Diphenyltriazene, not more than 40 parts per billion.

Lead (as Pb), not more than 10 parts per million.

Arsenic (as As), not more than 3 parts per million.

Mercury (as Hg), not more than 1 part per million.

Total color, not less than 87 percent.

- (2) FD&C Yellow No. 5 Aluminum Lake shall be prepared in accordance with the requirements of §82.51 of this chapter.
- (c) Uses and restrictions. (1) FD&C Yellow No. 5 may be safely used for coloring cosmetics generally, including cosmetics intended for use in the area of the eye, in amounts consistent with current good manufacturing practice.
- (2) FD&C Yellow No. 5 Aluminum Lake may be safely used for coloring cosmetics intended for use in the area of the eye, subject to the restrictions on use of color additives in §70.5(b) and (c) of this chapter, in amounts consistent with current good manufacturing practice.
- (d) *Labeling*. The label of the color additive shall conform to the requirements of §70.25 of this chapter.
- (e) Certification. All batches of FD&C Yellow No. 5 shall be certified in accordance with regulations in part 80 of this chapter.

[50 FR 35782, Sept. 4, 1985, as amended at 51 FR 24524, July 7, 1986; 59 FR 60898, Nov. 29, 1994]

§74.2706 FD&C Yellow No. 6.

- (a) Identity and specifications. The color additive FD&C Yellow No. 6 shall conform in identity and specifications to the requirements of §74.706 (a)(1) and (b).
- (b) Uses and restrictions. FD&C Yellow No. 6 may be safely used for coloring cosmetics generally in amounts consistent with current good manufacturing practice.
- (c) Labeling. The label of the color additive shall conform to the requirements of §70.25 of this chapter.
- (d) Certification. All batches of FD&C Yellow No. 6 shall be certified in ac-

cordance with regulations in part 80 of this chapter.

[51 FR 41782, Nov. 19, 1986]

§74.2707 D&C Yellow No. 7.

- (a) Identity and specifications. The color additive D&C Yellow No. 7 shall conform in identity and specifications to the requirements of §74.1707(a)(1) and (b).
- (b) Uses and restrictions. D&C Yellow No. 7 may be safely used for coloring externally applied cosmetics in amounts consistent with good manufacturing practice.
- (c) Labeling. The label of the color additive shall conform to the requirements of §70.25 of this chapter.
- (d) Certification. All batches of D&C Yellow No. 7 shall be certified in accordance with regulations in part 80 of this chapter.

§74.2707a Ext. D&C Yellow No. 7.

- (a) *Identity and specifications*. The color additive Ext. D&C Yellow No. 7 shall conform in identity and specifications to the requirements of §74.1707a (a)(1) and (b).
- (b) Uses and restrictions. Ext. D&C Yellow No. 7 may be safely used for coloring externally applied cosmetics in amounts consistent with good manufacturing practice.
- (c) Labeling. The label of the color additive shall conform to the requirements of §70.25 of this chapter.
- (d) Certification. All batches of Ext. D&C Yellow No. 7 shall be certified in accordance with regulations in part 80 of this chapter.

§74.2708 D&C Yellow No. 8.

- (a) Identity and specifications. The color additive D&C Yellow No. 8 shall conform in identity and specifications to the requirements of §74.1708(a)(1) and (b).
- (b) Uses and restrictions. D&C Yellow No. 8 may be safely used for coloring externally applied cosmetics in amounts consistent with good manufacturing practice.
- (c) Labeling. The label of the color additive shall conform to the requirements of §70.25 of this chapter.